

589.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake /Kabylake CPU, DDR4 up to 32GB, support max 4K display resolution
- Intel® Skylake /Kabylake Processor (Max. TDP 65W)
- Support DDR4-2133, 2 * SO-DIMM slot, up to 32GB memory
- 2 * USB2.0 , 4 * USB3.0 , 2 * COM , 1 * HDMI , 2 * DP , 2 * RJ45 , 1 * MIC , 1 * Line out , 1 * Line in , 4 * COM (Option)
- M/B Form Factor : Mini ITX (170x170mm)
- DC-19V_120W Adapter

MB Model	-JNF697-Q170 / Mini ITX
Part No	-HBJC142F697-Q170B (non-WIFI) -HBJC142F697W-Q170B (WIFI)
BIOS	-AMI 16MB SMT Flash ROM
CPU/Chipset	-Intel® LGA1151 Skylake /Kabylake Processor (Max. TDP 65W) -Intel® Q170 Express Chipset
Memory	-2 * SO-DIMM slots DDR4-2133 up to 32GB
Storage	-2 * 2.5" SATA3 6Gb/s internal drive bay
Network	-2 * Intel® GbE (i211AT * 1 & i219LM * 1) -1 * Full-size Mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model / Optional)
Rear Panel I/O	-4 * USB 3.0 ports -1 * HDMI, 2 * DP -2 * RJ45 -1 * Line-in, 1 * Line-out, 1 * Mic-in (Realtek ALC662VD) -2 * COM (RS232/422/485), 4 * COM (RS232/Optional) -2 * Antenna holes (WiFi model only) -19V DC-In jack
Front Panel I/O	-1 * Power button, 1 * Reset button -1 * Power LED, 1 * HDD LED -2 * USB2.0 ports
Internal I/O	-1 * SIM Card
Option	-TPM 1.2 / TPM 2.0

Power Source	-FSP DC Adapter / DC19V-6.3A-120W / LV6 -AC 90~240V input
Compliance	-CE, FCC, LVD, RoHS
Safety	-Vibration test: N.C -Shock test: N.C
Temperature	-Operating Temperature: 0~50°C -Storage Temperature: -10-70°C
Dimensions	-330 (W) x 192 (D) x 44 (H) mm
Packing	-Net Weight: 2.0KG -Gross Weight: 3.2KG -Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm
OS Support	-32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux