

369.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake N3350/N4200 SoC Processor
- Support 1 \* DDR3L 1866MHz SO-DIMM up to 8GB
- 2 \* USB3.0 ,1 \* GbE LAN ,1 \* HDMI , 1 \* Micro SIM
- Support M.2 (M-key, SATA interface, 2242) storage
- M/B Form Factor : PICO SBC (100x72mm)
- DC-12V\_40W Adapter

|                 |   |
|-----------------|---|
| MB Model        | - JNP691-3350 / PICO SBC<br>- JNP691-4200 / PICO SBC  |
| Part No         | - HBJC400P691-335B / HBJC400P691-420B (non-WIFI)<br>- HBJC400P691W-335B / HBJC400P691W-420B (WIFI)  |
| BIOS            | - AMI Flash ROM   |
| CPU/Chipset     | - Intel® Apollo Lake N3350/N4200 SoC Processor  |
| Memory          | - 1 * DDR3L-1866 SO-DIMM slots up to 8GB total  |
| Storage         | - 1 * M.2 – 2242 (M-KEY)  |
| Expansion Slot  | - 1 * Full-size mini-PCIE slot (for 802.11 b/g/n + BT 4.0 installed in WIFI model)  |
| Network         | - 1 * Realtek RTL8111H GbE  |
| Rear I/O Port   | - 2 * USB 3.0 ports<br>- 1 * HDMI (Max. resolution: 3840x2160@30Hz)<br>- 1 * RJ45<br>- 1 * SIM Card Holder<br>- 1 * Kensington lock<br>- 3 * Antenna holes<br>- 1 * DC Jack |
| Front Panel I/O | - 1 * Power button<br>- 1 * Power LED   |
| Power Source    | - AC-DC FSP Adapter / DC12V-3.3A-40W<br>- AC 90~240V input  |
| Compliance      | - CE, FCC, RoHS, ErP Ready  |
| Temperature     | - Operating Temperature : 0°C~50°C<br>- Storage Temperature : -20°C~70°C  |
| Dimensions      | - 129 (W) x 78.4 (D) x 34 (H) mm  |

---

|            |   |
|------------|---|
| Packing    | <ul style="list-style-type: none"><li>- Net Weight: 0.8KG</li><li>- Gross Weight■1.5KG</li><li>- Color Box Dimension■156 (W) * 167 (D) * 123.6 (H) mm</li></ul> |
| OS Support | <ul style="list-style-type: none"><li>- Windows 10 , Linux</li></ul>  |
| Warranty   | <ul style="list-style-type: none"><li>- 2 Year limited warranty</li></ul>   |