



698.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Comet Lake !
- Barebone !
- i5-10210U CPU !
- NEW VERSION !

12/22: New Version with Intel® I225-V 2.5GbE LAN

- Intel® Comet Lake i5-10210U 1.6G QC Processor
- 2\* DDR4 2666MHz up to 64GB
- 1\* Intel® I219LM GbE, 1\* Intel® I225-V 2.5GbE
- 1\* M.2 (M-key, SATA interface), 1\* M.2 (E-key, support CNVi)
- 1\* RS232/RS422/485, 4\* USB3.2
- Support 1\* DP, 2\* HDMI
- 12~24V DC-in

Model	<ul style="list-style-type: none"> <li>- HBJC330U95V-10210 (CPU : 10210U, default)</li> <li>- HBJC330U95VI-10210 (CPU : 10210U, Wifi)</li> <li>- HBJC330U95V-5205 (CPU : 5205U)</li> <li>- HBJC330U95VI-5205 (CPU : 5205U, Wifi)</li> </ul>
-------	---

CPU/Chipset	<ul style="list-style-type: none"> <li>- Intel® Comet Lake i5-10210U 1.6G QC SoC Processor</li> <li>- Intel® Comet Lake 5205U SoC Porcessor</li> </ul>
BIOS	- AMI 128MB SMT Flash ROM
Memory	- 2 * DDR4 2666MHz SO-DIMM up to 64GB
Network	<ul style="list-style-type: none"> <li>- 1* Intel® I219LM GbE</li> <li>- 1* Intel® I225-V 2.5GbE</li> </ul>
Graphics	<ul style="list-style-type: none"> <li>- 1* HDMI1.4 (Max Resolution : 4096x2304@30Hz)</li> <li>- 1* HDMI2.0 (Max Resolution : 4096x2304@60Hz)</li> <li>- 1* DP (Max Resolution : 4096x2304@60Hz)</li> <li>- Support Triple Displays</li> </ul>
Storage	- 1 * M.2 (M-Key, 2242, SATA interface)
Expansion	- N/A
Rear Panel I/O	<ul style="list-style-type: none"> <li>- 2 * USB3.2 (Gen2)</li> <li>- 1 * DP1.4</li> <li>- 1 * HDMI2.0</li> <li>- 1 * HDMI1.4</li> <li>- 2 * RJ45</li> <li>- 1 * DC Jack (12~24V)</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1 * Audio Jack (Line out +MIC)</li> <li>- 2 * USB3.2 (Gen2)</li> <li>- 1 * RS232/422/485</li> <li>- 1 * Power Button</li> </ul>
Internal Connector	<ul style="list-style-type: none"> <li>- 1 * M.2 (M-Key, SATA Interface)</li> <li>- 1 * M.2 (E-Key) for CNVi or PCI-E/USB WIFI/BT</li> <li>- 8bit GPIO</li> <li>- 2 * USB2.0</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- 12~24V DC-in</li> <li>- Adapter: DC 19V/6.32A 120W</li> </ul>
Compliance	- CE, FCC, RoHS, ErP Ready (Option)
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: -10 ~ 50° C</li> <li>- Storage Temperature: -20 ~ 60° C</li> </ul>
Dimensions	- 150 (W) x 106 (D) x 75 (H) mm
OS Support	- Windows 10, Linux