



999.00 FUR

incl. 19% VAT, plus shipping

- 1080p30!
- HDMI 1.4a!
- Mini PCI Express!

Support: <u>Datasheet</u>

1080P 60 FPS HDMI Video Capture CM311-H is a Mini-PCIe HDMI frame grabber capable of capturing videos up to 1080p@60. With AVerMedia Video Engine technology inside, it can perform various video processing tasks such as frame rate conversion, de-interlacing, scaling and so on without consuming the computing power of the target platform.

It is endowed with full functions that are required to capture Full HD video for industrial and commercial markets such as data recorders, medical imaging devices, machine vision or any industrial imaging applications. The CM311-H design is committed to shorten the development schedule and provide integrators with a complete and rugged solution towards building their own applications.

Mini PCIe Form Factor and Vibration-proof The compact form factor design of a Mini PCIe card is perfect for small-footprint embedded systems. It is also ideal for solutions that need to be vibration-proof while the mounting holes make it suitable for in-vehicle, military and industrial applications.

- Max capturing/ recording up to 1920 x 1080 60fps
- HDMI 1.4a input
- Mini PCI Express form factor
- Windows DirectShow compatible
- Specifically designed SDK

Host Interface
Audio Interface
Audio Format
Audio Sampling Rate
Connector Type
Video Input Interface

**Video Format** 

Color Depth Channel No.

Input Resolution

PCI Express Gen2 x1

**HDMI 1.4a** 

HDMI embedded audio 32KHz, 44.1KHz, 48KHz SHLD 30 pin connector

**HDMI** 

YUV444: IYU2, AYUV, V410, Y410

YUV422: YUY2, YUYV, UYVY, V210, Y210

YUV420: I420, NV12, YV12

**RGB: RGB565, RGB555, RGB24, RGB32, ARGB** 

8-bit/ 10-bit

1 Ch

1920x1080p @ 23.98/24/25/29.97/30/50/59.94/60 fps

1920x1080i @ 50/59.94/60 fps 1280x720p @ 50/59.94/60 fps

720x576p @ 50 fps

720x480p @ 59.94/60 fps

640x480p @ 59.94/60 fps

**Encoding Mode** 

**Accessories** 

**SDK kits** 

1920x1080 @ 23.98/24/25/29.97/30/50/59.94/60 fps

1280x720 @ 50/59.94/60 fps

**Record Resolution** 720x576 @ 50 fps

> 720x480 @ 59.94/60 fps 640x480 @ 59.94/60 fps **Software Encoding**

**Multi-Card Support** 

Yes Windows 7/8.1/10 (32/64 bits)\*

**Supported OS** 

Mini PCle Form factor Dimension (L x W) 50.80 x 30 mm

~ 4.0W **Power Consumption** 

**Operating Temperature** 0°C ~ 50°C (by simulation) **Operating Humidity** 5% ~ 80% Relative Humidity

**Ordering Information** CM311-H

Mini-PCle 1080p 60FPS HDMI Frame Grabber

30 pin to HDMI adapter cable

Thermal pad **SDK Basic SDK Pro** 

**SDK Premium Add-on Kits**