



689.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake-UP3 !
- 3x USB-C !
- 2x LAN !
- NUC Fromat !

- Intel® 11th Gen. Tiger Lake-UP3 SoC Processor
- 2\* DDR4 3200MHz SO-DIMM up to 64GB
- Rich and complete connection interface
- supports 4 sets of 4K HDR output
- 3\* internal M.2 expansion slots for various applications

|                |  |
|----------------|--|
| Model          | – N11-1115 (CPU : 1115G4)<br>– N11-1135 (CPU : 1135G7)   |
| CPU/Chipset    | – Intel® Tiger Lake-UP3 Processor  |
| BIOS           | – AMI Flash ROM  |
| Memory         | – 2* DDR4 3200MHz up to 64GB   |
| Network        | – 1* Intel i219-LM GbE<br>– 1* Intel i225-V 2.5GbE   |
| Graphics       | – Intel® UHD / Iris Xe Graphics, shared memory<br>– 2* HDMI 2.0b (Max Resolution: 4096x2160@60Hz)<br>– 2* DP1.4 (Max Resolution: 4096x2304@60Hz) from Type-C<br>– Support Four independent 4K HDR Displays |
| Storage        | – 1* M.2 M-key 2242/2280 (PCIe4.0 x4/SATAIII interface) support NVMe<br>– 1* 2.5" SATA Device ( <a href="#">support 2.5" HDD with a height ≤ 10mm</a> )  |
| Expansion slot | – 1* M.2 E Key 2230 for WiFi module<br>– 1* M.2 B Key 3042/3052 for 4G/5G module   |

|                    |   |
|--------------------|---|
| Rear Panel I/O     | <ul style="list-style-type: none"> <li>- 2* USB3.2 (Gen.2) Type-C support DP1.4 display output</li> <li>- 1* SIM Card slot</li> <li>- 2* HDMI 2.0</li> <li>- 2* RJ45</li> <li>- 1* DC Jack</li> </ul>             |
| Front Panel I/O    | <ul style="list-style-type: none"> <li>- 1* Audio (Line out +MIC combo)</li> <li>- 2* USB3.2 / A type (Gen.2)</li> <li>- 1* USB3.2 / C type (Gen.2)</li> <li>- 1* Power Button</li> <li>- 1* Power LED</li> </ul> |
| Internal Connector | <ul style="list-style-type: none"> <li>- 1* SATAIII</li> <li>- 1* AT/ATX mode jumper</li> <li>- Onboard TPM2.0 (option)</li> </ul>  |
| Compliance         | - CE, FCC, RoHS, ErP Ready  |
| Power Source       | <ul style="list-style-type: none"> <li>- MB : DC12~24V input</li> <li>- Adapter : DC12V_90W</li> </ul>  |
| Compliance         | - CE, FCC, LVD, RoHS  |
| Temperature        | <ul style="list-style-type: none"> <li>- Operating Temperature: -10 ~ 50° C</li> <li>- Storage Temperature: -20 ~ 60° C</li> </ul>  |
| Dimensions         | <ul style="list-style-type: none"> <li>- System: 121 (W) x 113.4 (D) x 59 (H) mm</li> <li>- Box: 244 (W) x 183 (D) x 118 (H) mm</li> </ul>  |
| OS Support         | - Windows 11, Linux   |
|                    |   |