169.80 EUR
incl. 19% VAT, plus shipping

This Delock CFast Flash Card supports the new CFast 2.0 standard and allows even higher data transfer rates than memory cards of the previous CFast generation. It is therefore ideally suited not only for professional usage in photography, but also for all other applications that require fast read and write speeds. CFast 2.0 memory cards use the SATA 6 Gb/s protocol and convince with lower power consumption.

Specification
• Capacity: 64 GB
• Memory chip: Toshiba MLC, 2 channels
• Controller: ID107
• CFast 7+17pin interface / SATA 6 Gb/s
• Supports CFast 2.0
• Operating voltage: 3.3 V
• Operating temperature: -40 °C ~ +85 °C
• Storage temperature: -55 °C ~ +95 °C
• Endurance:
Write / Erase: > 3,000 cycles
Read: unlimited
• Supports Write Protect, ATA Security and SMART (Self-Monitor Analysis and Reporting Technology)
• 310 MB/s read, 150 MB/s write
• Power consumption: 1.1 W (max.)
• Current demand:
Read: 240 mA
Write: 320 mA
Idle: 110 mA
• MTBF: > 3.000.000 hrs.
• Vibration: 20 G, 7 ~ 2000 Hz
• Shock: 1,500 G / 0.5 ms
• Dimension (LxWxH): ca. 36.4 x 42.8 x 3.6 m